PJD6251

LIGHT BRIGHT AND PORTABLE PROJECTOR

120HZ, 3D-READY

Brilliant, bright image. Easy maintenance.

The advanced PJD6251 120Hz / 3D ready DLP projector includes BrilliantColor™ technology to produce more vibrant colors. The HDMI port provides high quality content. And the ultra-high brightness and contrast ratios make this projector shine in virtually any lighting situation. This projector offers table top and ceiling or wall mount options. Making it ideal for classrooms and meeting rooms. The top load lamp and filter-less design provides for easy maintenance and low total cost of ownership. RJ-45 connectivity enables remote network control, while the extensive input options and integrated 2x5W speaker provide for effective presentations or classroom lessons. This projector also features closed captioning for the hearing impaired. Choose the PJD6251 for both classroom or corporate settings.

Versatile presentations anywhere

> **Bright in virtually any setting with lumens**
Packs 3700 ANSI lumens in just 2.95kg(6.5lb), and with a high 2800:1 contrast ratio, your presentations are guaranteed to be vibrant even in the brightest office environment.

> **BrilliantColor technology**
Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid color reproduction.

> **Eco-mode extends lamp life hrs**
Extend the life of your lamp up to 5000 hours** and reduce noise output.

> **Network control through RJ-45**
Remotely schedule, manage and monitor the projector and its lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

> **Off to go**
The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.

2800:1 Dynamic Contrast Ratio

MORE THAN 2000 AWARDS

VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic® See the difference™

PJD6251

LIGHT BRIGHT AND PORTABLE PROJECTOR

ViewSonic®
See the difference™

Model No.VS124585

DISPLAY	Type	0.55" Digital Micromirror Device(DLP™)
	Resolution	XGA 1024×768(Native) / SXGA 1600×1200(compressed)
	Lens	1.2 × Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction:+/- 40 degrees
	Display Size(diagonal)	30"-300"
	Throw Distance	1m-10m
	Throw Ratio	1.6-1.9
	Lamp	230watt(RLC-049)
	Lamp Life(Normal / Eco Mode)	4000 / 5000(hours)
	Brigtness	3700 Lumens
	Contrast Ratio	2800:1
	Aspect Ratio	4:3(native) & 16:9
	Color Depth	24 bits, 16.7M Colors(8+8+8)
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Gamut	85 % NTSC 1931 CIE
AUDIO	Speaker	5W x 2
INPUT SIGNAL	Computer and video	NTSC M(3.58MHz), 4.43MHz, PAL(B, D, G, H, I, M, N, 60), SD 480i and 576i(24fps, 25fps and 30fps), ED 480p and 576p(24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25pfs and 30fps)
	Frequency	Fh:31-100KHz, Fv:50-120Hz
COMPATIBILITY	PC	VGA to UXGA
	Mac	Up to 1024×768(may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	HDMI	1 × HDMI 1.3
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	2 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1 × RS-232(9 Pin D-sub)
POWER	Voltage	90~240VAC(Auto Switching), 50 / 60Hz(universal)
	Power Consumption	380W(Typical) / <1W(Stand-by mode)
LANGUAGE		English/ Dutch/ French/ Spanish/ Italian/ Korean/ Thai/ Portuguese/ T. Chines/ S. Chinese/ Japanese/ Russian/ German/ Swedish/ Turkish/ Finnish/ Polish
CONTROLS	Basic	POWER, Keystone/ Arrow keys, Left/ BLANK, MENU/ EXIT, Right/ Panel key lock, AUTO, MODE/ ENTER, SOURCE
	OSD	**Picture:** Brightness, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert. **Computer Image:** Frequency, tracking, H position, V position. **Video Image:** Saturation, sharpnes, tint. **Setting:** Manu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, ECO mode, high altitude, OSD timeout. **Advance:** Blank screen, password word, screen capture, start up screen, text shot, digital zoom, DCR, close captions, brilliant color,
OPERATING CONDITIONS	Temperature	0°C-40°C(32°F-104°F)
	Humidity	10%-90%(non-condensing)
	Altitude	0~1800m(6000ft), operational up to 3048m(10,000ft) at reduced reliability and performance
NOISE LEVEL	Normal / Eco Mode	34dB / 32dB
DIMENSIONS (W x H x D)	Physical	280×114×218(mm) / 11×4.5×8.58(inch)
WEIGHT	Net	2.95kg (6.5lb)
REGULATIONS		CB, ROHS, WEEE, UL / cUL, FCC-B, ICES-003, IRAM(Argentina), NOMPSB, C-tick, EK, CE, TUV / GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Soft case, Quick Start Guide, ViewSonic Wizard CD(with User Guide)
WARRANTY		3 years, 1years or 1000 hours

Optional Accessories

>Replacement Lamp.....RLC-051
>Wireless G Presentation Gateway.....WPG-350
>Ceiling mount.....WMK-025

Projection Distance		4 : 3 Screen Screen Size			
		Wide		Tele	
M	feet	m	inch	m	inch
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259

RoHS COMPLIANT

ISO 9001:2000 FM 40187
ISO 14001:1996 FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Rev.1.0

ViewSonic Europe Limited/UK
Tower 42
25 Old Broad Street
London EC2N 1HQ
United Kingdom
Tel: +44 (0)207 382 8250
Fax: +44 (0)207 382 8251

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
5 rue de Helder
75009 Paris
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +31 (0)20 491 9254
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required.

Copyright © 2009 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VX2268wm 07/09-UK